

GOLD COAST CHEMICAL PRODUCTS


A DIVISION OF DORA INDUSTRIES, INC.
 2790 S. PARK RD., PEMBROKE PARK, FL 33009
 (954)893-0044 EMERGENCY 1-800 255-3924

MATERIAL SAFETY DATA SHEET

HMIS SYMBOL

HEALTH	0
FLAMMABILITY	2
REACTIVITY	2

HMIS 4 NFPA
 SEVERE 3 EXTREME
 SERIOUS 2 HIGH
 MODERATE 1 MODERATE
 SLIGHT 0 SLIGHT
 MINIMAL 0 INSIGNIFICANT



MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATIONS STANDARD (HSC) 29 CFR 1910.1200

Trade Name KUUL TOOL CUTTING FLUID I — IDENTIFICATION FORMULA:
 Proprietary Mixture

II — HAZARDOUS INGREDIENTS

Principle Hazardous Components	CAS #	TLV	PEL	APPROX % WT
Isobutane/propane blend	75-28-5	800	800	
Petroleum Oil	74-98-6 64742-53-6	1000 5mg/M3	1000 5mg/M3	

III — PHYSICAL DATA

BOILING POINT: N/D
 VAPOR PRESSURE: In can psig @ 70°F max 60
 VAPOR DENSITY: N/D
 SOLUBILITY IN WATER: insoluble

SPECIFIC GRAVITY: H2O=1
 %VOLATILE BY VOLUME >80
 FLASH POINT: NA
 APPEARANCE AND ODOR: DARK OIL, WITH ODOR OF SULFUNIZED OILS

IV — FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS: L/L n/d U/L n/d

FLAMMABILITY: flammable
 EXTINGUISHING MEDIA: Water, Foam, Carbon Dioxide
 SPECIAL FIRE-FIGHTING PROCEDURE: self-contained breathing apparatus
 UNUSUAL FIRE AND EXPLOSION HAZARDS: do no expose aerosols to temperatures above 130°F or container may rupture

V — REACTIVITY DATA

CHEMICAL STABILITY: Stable
 CONDITIONS TO AVOID: open flame, welding arcs, heat.
 INCOMPATIBILITY (MATERIALS TO AVOID): strong oxidizers
 HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂ sulfur oxides.
 HAZARDOUS POLYMERIZATION: Will not occur

