

**GOLD COAST CHEMICAL PRODUCTS**


A DIVISION OF DORA INDUSTRIES, INC.  
 2790 S. PARK RD., PEMBROKE PARK, FL 33009  
 (954)893-0044 EMERGENCY 1-800 255-3924

**MATERIAL SAFETY DATA SHEET**

HMIS SYMBOL

HEALTH	0
FLAMMABILITY	2
REACTIVITY	1

HMIS 4 NFPA  
 SEVERE 3 EXTREME  
 SERIOUS 2 HIGH  
 MODERATE 1 MODERATE  
 SLIGHT 0 SLIGHT  
 MINIMAL 0 INSIGNIFICANT



MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATIONS STANDARD (HSC) 29 CFR 1910.1200

**Trade Name** TFE LUBRICANT (all purpose dry lubricant) I — IDENTIFICATION FORMULA:  
 Proprietary Mixture

II — HAZARDOUS INGREDIENTS

Principle Hazardous Components	CAS #	TLV	PEL	APPROX % WT
1,1,1,Trichloroethane	71-55-6	350		62%
Methylene Chloride	75-09-2	500		15%

III — PHYSICAL DATA

BOILING POINT: N.D. SPECIFIC GRAVITY: CONC @75° F 1.190  
 VAPOR PRESSURE: In Can psig @ 75° F 90 %VOLATILE BY VOLUME In Can 83.7  
 VAPOR DENSITY: N.D. FLASH POINT: OPEN CUP None up to 150° F  
 SOLUBILITY IN WATER: Slight APPEARANCE AND ODOR: Yellowish/sweetish odor

IV — FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS: L/L U/L

FLAMMABILITY: Flammable  
 EXTINGUISHING MEDIA: Foam, Dry Chemical, Carbon Dioxide  
 SPECIAL FIRE-FIGHTING PROCEDURE: None  
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None

V — REACTIVITY DATA

CHEMICAL STABILITY: Stable  
 CONDITIONS TO AVOID: Do not expose to temperatures above 120° F  
 INCOMPATIBILITY (MATERIALS TO AVOID):  
 HAZARDOUS DECOMPOSITION PRODUCTS: Open flames possible trace of phosgene.  
 HAZARDOUS POLYMERIZATION: Will not occur.

